



NOTES 1:

- UL Standard :
1. Rating: 300V 8A
 2. Insulation Withstands Voltage: AC 2000V at 1 minute
 3. Using Temperature Range: -40°C~+110°C

- IEC Standard :
1. Rating: 630V 15A
 2. Rate Impulse Voltage: 4000V
 3. Insulation Resistance: 500MΩ or more at DC500V
 4. Material Group : I
 5. Pollution Degree : 2
 6. Overvoltage Category: II
 7. Using Temperature Range: -40°C~+110°C

NOTES 2:

1. RoHS compliance

P	2	3	4	5	6	7	8	9
U	3.5	7.0	10.5	14.0	17.5	21.0	24.5	28.0
V	14.9	18.4	21.9	25.4	28.9	32.4	35.9	39.4
P	10	11	12	13	14	15	16	17
U	31.5	35.0	38.5	42.0	45.5	49.0	52.5	56.0
V	42.9	46.4	49.9	53.4	56.9	60.4	63.9	67.4
P	18	19	20	21	22	23	24	
U	59.5	63.0	66.5	70.0	73.5	77.0	80.5	
V	70.9	74.4	77.9	81.4	84.9	88.4	91.9	

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

4	NUT	STEEL	M2/Zn Plated
3	LIGHT BAR	PC	TRANSPARENT
2	SOLDER PIN 1	COPPER ALLOY	Tin Plated
1	HOUSING	PA+GF	UL94-V0 BLACK
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	LWF	DATE	16.07.25	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	3:1 (:)		
APP.		DATE		NAME		0225-11XXTH/14	
				DINKLE ENTERPRISE CO., LTD		DWG NO. SP-03-02251114	

REV.	CONTENT	NAME	DATE
------	---------	------	------